

## AIR-LUBE 32 & AIR-LUBE 68

### AIR TOOLS LUBRICANTS

**AIR-LUBE 32 & 68** are a special blend of premium mineral base fluids fortified with a synthetic additive system designed for the most demanding air tool applications.

**AIR-LUBE** oils are available in both ISO 32 and ISO 68 viscosities to accommodate both small and large air tools.

- AIR-LUBE 32 is for small drills, grinders, vibrators, wrenches, screw drivers, air nailers and staplers, air cylinders, motors, valves and chucks.
- AIR-LUBE 68 is for large drills, grinders, vibrators, hand-held tools and jackhammers

The featured physical properties of Air-Lube Oils provide the following benefits:

- Moisture in the compressed air is emulsified to protect metal surfaces and prevent rust.
- Enhanced extreme pressure properties protect tools from seizure and wear and provide good adherence to wet working surfaces.
- Elimination of lubricant oxidation prevents lost time due to gumming and varnishing.
- Proper atomization for good lubrication and control of fogging.
- Good low temperature properties to protect equipment in adverse weather conditions.
- Container sizes available in one gallon, 5 gallon pail and 55 gallon drum

### PHYSICAL PROPERTIES:

PRODUCT	AIR-LUBE 32	AIR-LUBE 68
ISO GRADE	32	68
Viscosity @ 40°C, cSt	31.93	69.40
Viscosity @ 100°C, cSt	5.37	8.88
Viscosity @ 100°F, SUS	165	359
Viscosity @ 210°F, SUS	44.3	56.2
Viscosity Index	101	101
Pour Point, °F (°C)	-5 (-21)	-0 (-18)
Flash Point, °F (°C)	430 (221)	430 (221)

### Petrochem, Inc.

6N999 Whispering Trail Road, St. Charles, IL 60175

Phone (630) 513-6350 Fax (630) 513-8324

Web [www.petrochem1.com](http://www.petrochem1.com)

Email [info@petrochem1.com](mailto:info@petrochem1.com)



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

**Member of the American Baking Society**