



TECHNICAL DATA

Rev.3/16

FOODSAFE SYNCOMP FG-46XL

SYNTHETIC FOOD GRADE ROTARY AIR COMPRESSOR LUBRICANT

FOODSAFE SYNCOMP FG-46XL (*Hydrocarbon -PAO*) air compressor lubricant is specially designed for rotary screw compressors in the food, beverage and packaging industry.

FOODSAFE SYNCOMP FG-46XL lubricant provide maximum protection, in an extremely tough environment, for your air compressors.

PRODUCT FEATURES:

- Approved by the U.S.D.A. for H-1 applications (lubricants with possible food contact), they comply with the requirements of F.D.A. 21 CFR 1778.3570
- Protects against wear, rust, corrosion, and provides excellent high temperature thermal stability, foam, and oxidation ability.
- Manufactured from high-quality hydrocarbon base fluids and proprietary additives
- Available in 5 gallon pail or 55 gallon drum

PHYSICAL PROPERTIES

Property	ISO 46 SAE 15W
Viscosity Index	130
Viscosity @ 40° C, cSt	46
Viscosity @ 100° C, cSt	8
Viscosity @ 100° F, SUS	235
Viscosity @ 210° F, SUS	52
Flash Point, ° F	505 (263)
Pour Point, ° F	-40
Auto ignition Point, ° F	745
Water Separation	40/40/0
Copper Corrosion	1A
4 Ball Wear (mm scar)	0.4
Color	Clear

HANDLING PRACTICES:

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet. For more information and availability, call (630) 513-6350.

Petrochem, Inc.

6N999 Whispering Trail Road, St. Charles, IL 60175

Phone (630) 513-6350 Fax (630) 513-8324

Web www.petrochem1.com

Email info@petrochem1.com



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

Member of the American Baking Society