

HT-300

HIGH TEMPERATURE SYNTHETIC OVEN CHAIN LUBRICANT

DESCRIPTION: 100% Synthetic, Fully Formulated, ISO 100 (30W), Oven and Industrial Lubricant. 1988 LANHAM MACHINERY, INC., & APV/TURKINGTON & BAKETECH APPROVED

APPLICATIONS: All ingredients used in HT-300 are USDA H2 approved.

- Bakery oven chains: Conventional (tunnel and tray ovens/bread and bun), Continuous roller ball bearing conveyor oven chains, ice cream cone ovens both ferris and sugar cone and corn/flour tortilla chains
- Tenter frames in textile plants; Roller chains on conveyor belts; Kiln support rollers in cement plants
- Sealed for life bearings; Drying oven chains for paint lines
- Lithographic chains for beverage can line ovens; Kiln car wheel bearings in refractory plants
- Many others

FEATURES & BENEFITS:

- Exceptional high temperature stability – HT-300 is made from polyol esters and does not use polymers to build viscosity or viscosity index. This feature results in a reduction to form carbon and varnish deposits in high temperature applications.
- Cleanliness – HT-300 is an ashless lubricant, which helps to eliminate accumulation of solids that create maintenance clean-up problems and downtime. It is often credited with helping to clean chains already dirtied by inferior lubricants.
- Low Volatility – Provides longer lubrication intervals, reduced consumption, less smoke and no odors.
- Energy efficient – Reduces equipment energy consumption.
- Protection against – Rust, wear, oxidation and corrosion. Extends equipment life and reduces maintenance costs.
- Optimum viscosity – Excellent for lower and higher temperatures than regular petroleum oils.
- USDA Authorized – HT-300 is authorized by USDA for use in federally inspected meat and Poultry plants.

HT-300 SPECIFICATION PROPERTIES:

Property	Typical Specification	Test Method
SAE Viscosity Grade	30 (ISO 100)	
Evaporation Loss, wt. % (6 ½ hours @400°F)	1.5	ASTM D972
Evaporation Loss, wt. % (20 hours @450°F)	9.5	ASTM D972
Flash Point °C, C.O.C. (°F)	308°C (586°F)	ASTM D92
4 Ball Wear Scar, MM- 1 Hour, 1200 rpm, 40 Kg, 75 C (167F)	0.3	ASTM D972
Density, lbs./USG @ 15.6°C (60°F)	8.10	ASTM D1298

Petrochem, Inc.

6N999 Whispering Trail Road, St. Charles, IL 60175

Phone (630) 513-6350 Fax (630) 513-8324

Web www.petrochem1.com

Email info@petrochem1.com



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

Member of the American Baking Society

Viscosity @ 210°F., SUS @ 100°F., SUS	69 351	ASTM D445 ASTM D445
Viscosity @ 210°F., cSt @ 100°F., cSt	10.8 82	ASTM D445 ASTM D445
Viscosity Index	145	ASTM D2270
Pour Point °F	-32	ASTM D97
Fire Point °C (°F)	338 (6640)	ASTM D92
Ash Weight %	<0.01	ASTM D482
Rust Test, 48 Hours Distilled Water Sea Water	Pass Pass	ASTM D665A ASTM D665B
Appearance	Clear Amber liquid	QL4099