



# TECHNICAL DATA

Rev.5/12

## FOOD GRADE TROLLEY LUBE 46 FORMULATED WITH USP GRADE WHITE OILS

PETROCHEM'S TROLLEY LUBE 46 is formulated using high purity USP grade white oils and is fortified with anti-oxidant, anti-wear and anti-corrosion additives.

### APPLICATIONS:

PETROCHEM'S TROLLEY LUBE 46 is an ISO 46 fluid used to lubricate a variety of applications including (but not limited to):

- Trolley conveyors and chains throughout the meat, poultry and fish industries
- Hook wheels
- NSF H-1 and meets all FDA requirements under 21 CFR 178.3570 for lubricants with incidental contact with food.
- Packaging Available in 5 gallon pail or 55 gallon drum

### PROPERTIES:

Property	Test Method	Typical Specification
ISO Viscosity Grade	ASTM D2422	46
Viscosity, cSt. 40°C	ASTM D445	45
100°C	ASTM D445	7.31
Saybolt Viscosity @ 100 °F	ASTM D2270	240
Pour Point °C/°F	ASTM D97	-48 (-54)
Flash Point °C/°F	ASTM D92	246 (475)

### HANDLING PRACTICES:

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet. For more information and availability, call (630) 513-6350.

### Petrochem, Inc.

6N999 Whispering Trail Road, St. Charles, IL 60175

Phone (630) 513-6350 Fax (630) 513-8324

Web [www.petrochem1.com](http://www.petrochem1.com)

Email [info@petrochem1.com](mailto:info@petrochem1.com)



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

*Member of the American Baking Society*