



Our Business is
Global

TECHNICAL DATA

PETRO-GARD® FMG-2

SEMI-SYNTHETIC FOOD GRADE ALUMINUM COMPLEX GREASE

FOODSAFE PETRO-GARD® FMG-2 grease is an aluminum complex thickened semi-synthetic lubricating grease created specifically for the pharmaceutical, food service, bakeries, dairy, meat and poultry, beverage, and packaging industries. The aluminum complex thickener system provides excellent water resistance and a broad operating temperature range from -30°C to 148°C (300°F). NSF H1 registered for incidental contact with food in and around food processing areas.

A combination of newly developed additives and dependable BX1 additives provide excellent anti-wear/extreme pressure properties, oxidation resistance, and corrosion prevention. Special additives are employed to keep the grease in place between wash-down cycles which improves equipment and lubricant life in wet conditions.

Physical Properties

SEMI-SYNTHETIC FOOD GRADE GREASE	PETRO-GARD® FMG-2
NLGI Grade	2
ISO GRADE	220
Color	White to slightly off white
Texture	Homogenous
Base Oil -ASTM D 446	Mineral Oil/PAO
Viscosity at 40°C cSt	138 cSt
Viscosity at 100°C cSt	17.5 cSt
Viscosity Index	140
Thickener Type	Aluminum Complex
Density at 20°C g/cm3	0.97
Service Temperature	-30°C to 148°C (300°F)
Drop Point -ASTM D 2265	270C (518F)
Penetration Worked 60 ds	280 1/10 mm
Prolong worked 100,000 ds ASTM D 217	308 1/10 mm
Oil Separation -ASTM D6184	< 3%
4-Ball Wear - ASTM D 2266	0.47mm
4-Ball Load Wear Index	64.3
Last non seizure load	100-kg
Last seizure load	400-kg (2.02mm)
Weld load, kg ASTM D 2596	400 kg
Corrosion Preventative Properties – ASTM D 1743	Pass
Corrosion Preventative Properties EMCOR ASTM D 6138	0/0
Water Washout – ASTM D 1264	3%
NSF Registered (Approved for incidental contact with food)	H1



PETROCHEM, INC.
SPECIALTY LUBRICANTS

6N999 Whispering Trail Road, St. Charles, IL 60175
Phone: 630.513.6350 Fax: 630.513.8324
www.petrochem1.com info@petrochem1.com

The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem disclaims all Liability incurred in connection with the use of this data or suggestions.

Member of the American Baking Society

