

AIR-COMP SERIES

SEMI-SYNTHETIC AIR COMPRESSOR OILS

Petrochem's **AIR-COMP AIR COMPRESSOR OILS** are a premium synthetic blend of synthetic, and petroleum base fluids specially designed for compressor applications and are useful in multi-purpose applications.

AIR-COMP 32, 46, 68 & 100 lubricants are manufactured using the highest quality base stocks, additive treated with rust and corrosion inhibitors, oxidation control agents, anti-wear compounds and defoamants and is exceptional at controlling sludge and deposits.

AIR-COMP 32, 46, 68 & 100 are recommended for rotary screw, vane and reciprocating air compressors. Offers a service life of up to 4,000 hours under a wide range of temperatures and good operating conditions.

AIR-COMP 32, 46, 68 & 100 are REPLACEMENT/generic alternative to brands such as: **Kaeser M-460®**, **Sullair SRF 1/4000®**, **Atlas Copco GA-4K®**, and **Gardner Denver AEON 4000®**. (® Trademarks)

Container sizes: 1 gallon, 5-gallon pail and 55-gallon drum

PHYSICAL PROPERTIES:

AIR-COMP Property	TEST METHOD	32	46	68	100
ISO Viscosity Grade	ASTM D2422	32	46	68	100
Viscosity Index	ASTM D2270	146	97	99	97
Viscosity @ 40° C, cSt	ASTM D445	32	45.8	64	97.2
Viscosity @ 100° C, cSt	ASTM D445	6	6.7	8.3	10.9
Flash Point, ° F (°C)	ASTM D92	216 (420)	460 (238)	480 (249)	500 (260)
Pour Point, ° F (°C)	ASTM D97	-40 (-40)	-33 (-36)	-27 (-33)	-27 (-33)
Four Ball Wear Test	ASTM D2266	0.60	0.60	0.50	0.50
Emulsion Tendency	ASTM D1401	40/40/0 10 mins.	40/40/0 10 mins.	40/40/0 10 mins.	40/40/0 10 mins.

HANDLING PRACTICES:

For information on the safe handling and use of this product, refer to the Safety Data Sheet.
For more information and availability, call (630) 513-6350.

Petrochem, Inc.

333 North Randall Road, St. Charles, IL 60174

Phone (630) 513-6350 **Fax** (630) 513-8324

Web www.petrochem1.com

Email info@petrochem1.com



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

Member of the American Baking Society