

AIR-TOOL 22

AIR TOOL LUBRICANT

Petrochem's **AIR-TOOL 22** is an air tool lubricant specifically designed to provide superior lubrication for rotary and reciprocating types of air tools. Application is done by feeding the lubricant directly through an air line lubricator or by applying oil directly into the air tool through quick-coupling air line connections.

Applications Include: Air Motors, Impact Wrenches, Grinders, Reamers, Drills, and Chipping Hammers

The featured physical properties of Air-Tool 22 provide the following benefits:

- Compatible with petroleum oils and polyalphaolefins (PAOs)
- Engineered with the unique operational demands of air tools
- Offers enhances protection against rust and wear while being formulated for improved long-term stability.

Container sizes: 1 gallon and 5-gallon pail

PHYSICAL PROPERTIES:

AIR-TOOL Property	TEST METHOD	22
ISO Viscosity Grade	ASTM D2422	22
Viscosity Index	ASTM D2270	77
Viscosity @ 40° C, cSt	ASTM D445	22.9
Viscosity @ 100° C, cSt	ASTM D445	4.1
Flash Point, ° F (°C)	ASTM D92	194 (380)
Pour Point, ° F (°C)	ASTM D97	-40 (-40)
Specific Gravity	ASTM D4052	0.86

HANDLING PRACTICES:

For information on the safe handling and use of this product, refer to the Safety Data Sheet.
For more information and availability, call (630) 513-6350.

Petrochem, Inc.

333 North Randall Road, St. Charles, IL 60174

Phone (630) 513-6350 **Fax** (630) 513-8324

Web www.petrochem1.com

Email info@petrochem1.com



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

Member of the American Baking Society