

TECHNICAL DATA

PETRO-COMP FG-40XL

Rev. 06/19

FOOD GRADE SYNTHETIC (PAO) LONG-LIFE COMPRESSOR OIL

PETRO-COMP FG-46XL is a premium fully synthetic PAO air compressor lubricant designed for extended long life lubrication for rotary screw compressors in the food, beverage and packaging industry.

PETRO-COMP FG-46XL lubricant provides maximum wear protection and excellent lubricity compared to other H-1 food grade synthetic oils allowing 50% to100% increase in lubrication service life.

PRODUCT FEATURES:

- Formulated from the highest quality Polyalphaolefin (PAO) base oils with a superior proprietary additive package to achieve long life and oxidation stability.
- Service life of up to 8,000 service hours in good operating conditions.
- Available in 1 gallon containers, 5 gallon pail or 55 gallon drum

PETRO-COMP FG-40XL is a replacement/generic alternative to brands such as: Quincy Quinsyn F®, Sullair FG, Ingersoll-Rand Ultra FG® or X-Tend FG Coolant®, Atlas Copco GA-FG®, and Gardner Denver AEON 6000FG®.

PHYSICAL PROPERTIES

Property	Test Method	ISO 46 SAE 15W
ISO Grade	ASTM D2422	46
Viscosity @ 40° C, cSt	ASTM D445	45.5
Viscosity @ 100° C, cSt	ASTM D445	7.5
Viscosity Index	ASTM D2270	130
Flash Point, ° C / ° F	ASTM D92	263 / 505
Pour Point, ° C / ° F	ASTM D97	-40 / -40
Emulsion Tendency	ASTM D1401	40/40/0
Rust	ASTM D665B	PASS
Copper Corrosion	ASTM D130	1A
Four Ball Wear, 40 Kg., 1200 rpm, 75° C, 1 hr., Scar Diameter, mm	ASTM D4172	0.40
Specific Gravity	ASTM D1298	0.85
Color	Visual	Clear

HANDLING PRACTICES:

For information on the safe handling and use of this product, refer to the Safety Data Sheet. For more information and availability, call (630) 513-6350.







The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.