

TECHNICAL DATA

FOODSAFE PR FG-15

Rev.06/19

SYNTHETIC FOOD GRADE DRY PROOFER CHAIN LUBRICANT

DESCRIPTION: (ISO 15, SAE 5W) NSF H-1 REGISTERED

PRODUCT APPLICATION: PR FG-15 lubricant is specially formulated for tortilla and bakery dry proofer chain applications where incidental food contact may occur. 100% fully synthetic providing maximum protection.

Apply lubricant automatically, manually or best method. Adjust your lubrication cycles to take advantage of PR-15 reduced lubrication consumption.

PRODUCT FEATURES:

- The lighter weight viscosity prevents chains from stretching caused by excess loads of build-up from flour, sesame seeds and other airborne debris sticking to the chain.
- Outperforms regular lubricants and significantly reduces lubricant consumption
- NSF H-1 registered, meets USDA H-1 1998 guidelines where incident contact with food may occur. Complies with the requirements of F.D.A. 21 CFR 1778.3570.
- Colorless, Odorless and manufactured from high quality Hydrocarbon base stock and selective additives for enhanced performance.
- Superior anti-wear additives to protect chain from seizure and wear and provides good adherence to the chain or metal surfaces.
- Enhanced rust, oxidation and corrosion inhibitors preventing gumming, varnishing and rusting.
- Available in 5 gallon pail or 55 gallon drum

PHYSICAL PROPERTIES:

Property	Test Method	PR FG -15 ISO 15 (SAE 5W)
Viscosity Index	ASTM D2270	122
Viscosity @ 40° C, cSt	ASTM D445	15.0
Viscosity @ 100° C, cSt	ASTM D445	3.58
Viscosity @ 100°F, SUS	ASTM D445	82
Viscosity @ 210°F, SUS	ASTM D445	38.3
Flash Point, ° F	ASTM D92	370
Fire Point, °F	ASTM D92	430
Pour Point, ° F	ASTM D97	-85
Specific Gravity	ASTM D1298	0.816
Color	ASTM D1500	Clear

HANDLING PRACTICES:

For information on the safe handling and use of this product, refer to the Material Safety Data Sheet. For more information and availability, call (630) 513-6350.





