

PETRO-COMP SERIES

AIR COMPRESSOR OILS

The **Petrochem PETRO-COMP Series** are formulated from highly refined hydro-cracked base stocks and the unique additive **SYNTHOLATE**. The addition of **SYNTHOLATE** inhibits the formation of varnish and carbon and provides superior thermal and oxidative stability. Utilizing the superior petroleum base stocks fortified with **SYNTHOLATE** extends the life of the compared to that of conventional mineral oils and provides the following money saving benefits:

- Improved rust and oxidation protection versus general or multi-purpose R&O circulation oils.
- Reduced lubricant consumption - Extended drain intervals and lower vapor pressure reduce lubricant consumption.
- Reduced maintenance - **SYNTHOLATE** reduces carbon and varnish formation thus extending valve life and the time interval between overhauls.
- Eliminates recompression - **SYNTHOLATE** keeps the valves clean and eliminates the primary cause of recompression.
- Reduced power consumption - Elimination of recompression and reduced coefficient of friction result in less power consumption per unit of compression.
- Improved safety - Higher flash points provide a greater margin of safety in air compression.

PETRO-COMP 46, 68, 100 are recommended for rotary screw, vane and reciprocating air compressors. Offers a service life of up to **1,500 hours** under good operating conditions.

PETRO-COMP 68 is a REPLACEMENT/generic alternative to brands such as: **Atlas Copco Roto Inject**, **Gardner Denver AEON E21 2000®**, **Ingersoll-Rand SL-200®**, **Leroi SSL 38®**, **Qunicy Cip 68®** (® Trademarks)

Container sizes: 1 gallon, 5-gallon pail and 55-gallon drum

PHYSICAL PROPERTIES:

AIR-COMP Property	TEST METHOD	46	68	100
ISO Viscosity Grade	ASTM D2422	46	68	100
Viscosity Index	ASTM D2270	97	99	68
Viscosity @ 40° C, cSt	ASTM D445	46	66	99
Viscosity @ 100° C, cSt	ASTM D445	6.7	8.5	8.5
Flash Point, ° F (°C)	ASTM D92	470 (243)	470 (243)	520 (271)
Pour Point, ° F (°C)	ASTM D97	-25 (-32)	-38 (-38)	-38 (-38)
Four Ball Wear Test	ASTM D2266	0.60	0.60	0.60
Emulsion Tendency	ASTM D1401	40/40/0 10 mins.	40/40/0 10 mins.	40/40/0 10 mins.

HANDLING PRACTICES: For information on the safe handling and use of this product, refer to the Safety Data Sheet. For more information and availability, call (630) 513-6350.

Petrochem, Inc.

333 North Randall Road, St. Charles, IL 60174

Phone (630) 513-6350 Fax (630) 513-8324

Web www.petrochem1.com

Email info@petrochem1.com



The information contained herein is believed to be accurate but all suggestions are made without Guarantee because the conditions of actual use are beyond our control. Petrochem, Inc. disclaims all Liability incurred in connection with the use of this data or suggestions.

Member of the American Baking Society