

TECHNICAL DATA SHEET



FOODSAFE® PFPE 9000CL

FOODSAFE PFPE 9000CL is a Perfluoropolyether (PFPE) based, high temperature chain lubricant fortified with Polytetrafluoroethylene (PTFE). It has been formulated with a proprietary blend of PFPE oils and enriched with a fluid compatible corrosion inhibitor to provide easy application and long life for demanding applications.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. NSF Registration No. 170816; Category Code: H1.

Key Features and Benefits:

- Significant extended lubrication intervals
- Excellent Thermo-Oxidative Stability
- High Melting Point Thickener System
- Auto-Lube Compatible

- No Flashpoint
- Does not smoke and no odors
- Does Not Carbonize
- Formulated for extreme high temperatures

Bakery Oven Chain Applications:

All Food Processing Equipment

- Tortilla
- Continuous
- Bagel/Muffin
- Hotcakes
- Tray

- Tunnel
- Pita
- Rack
- Spiral
- Pizza

Packing Sizes:

Container	U.S.	Metric
Jug	11 lb	5 kg
Pail	55 lb	25 kg
Custom packaging available upon request.		



333 North Randall Road • St. Charles, IL 60175
PHONE: 630.513.6350 • FAX: 630.513.8324
www.petrochem1.com • info@petrochem1.com

Typical Properties of FOODSAFE PFPE 9000CL

Property	Method	Typical Value
Color	Visual	Milky White
Appearance	Visual	Pourable Liquid
Base Oil Type	Report	PFPE
Base Oil Kinematic Viscosity, 40°C/ °104 F	ASTM D445	227.5 cSt
Base Oil Kinematic Viscosity, 100°C/°212 F	ASTM D445	25.61 cSt
Base Oil Kinematic Viscosity, 250°C/°482 F	ASTM D445	3 cSt
Base Oil Viscosity Index	ASTM D2270	143.4
Base Oil Pour Pint	ASTM D97	143.4
Flash Point	Report	Does Not Flash

Safety:

If fumes are generated at elevated temperatures, ventilation is required. See the Safety Data Sheet for additional safety related information for this product.

Disclaimer:

Since we are unable to anticipate or control the conditions under which this information and our products may be used, we cannot guarantee the applicability of this information or suitability of our products in any specific application. Moreover, the products are sold without warranty, expressed or implied. Statements concerning the possible use of our products are not intended as recommendations to use our product in the infringement of any patent.

02/2024